

MAXIMO FENCE & GATE CARE & MAINTENANCE



MAXIMO Fences and Gates are manufactured from low maintenance, weather resistant aluminium which offers years of use and visual appeal. This simple maintenance programme is to preserve the longevity and good looks of your fencing or gate.

MAINTENANCE:

Regular visual inspections will help to identify and address any issues before they become serious, particularly if you have installed gates or fences around a pool area. All pool owners are required to ensure their pool gates and fences continue to meet NZ pool fencing standards, through ongoing maintenance and repairs.

Gate hardware requires regular cleaning to overcome the effects of environmental damage such as pollution, ultraviolet light and salt deposits. Cleaning should take place every six months and every three months in more harsh environments, such as seaside or industrial areas.

CLEANING GATE HARDWARE:

- 1 - Remove loose deposits with a wet sponge rather than risk scratching the surface by dry dusting.
 - 2 - Use a soft brush and mild detergent in warm water, to clean the surface and remove dirt and deposits.
 - 3 - Rinse with fresh water.
 - 4 - If necessary, add lubrication to hinges etc to help gates work easier.
- DO NOT use detergents on plated products
DO NOT use solvents or harsh detergents on the product.

CLEANING ALUMINIUM FRAME:

- 1 - Carefully remove any loose deposits with a wet sponge.
 - 2 - Wash down using a nonabrasive soft brush and a mild household detergent solution to remove dust, salt, dirt and other deposits.
 - 3 - Anodised finishes with greasy deposits or hard to remove grime, should be cleaned with a soft cloth dipped in white spirit, turpentine or kerosene, then wiped with a dry rag.
 - 4 - Rinse off with plenty of clean fresh water.
 - 5 - Wiping over with an absorbent cloth/chamois will prevent water marks from forming.
- DO NOT under any circumstances use abrasive scouring pads, cleaners or caustic solutions, as these will cause permanent damage to the finish.
DO NOT use solvents or harsh detergents on any of the MAXIMO Gate Frames.
DO NOT use aggressive solvents, thinners, petrol etc, on powder coating as these solvents will attack gloss levels and reduce its life expectancy.
DO NOT let any solvents used on anodised finishes come into contact with any rubber components as they can degrade them.
DO NOT expose your anodised/powder coatings to excessive heat, heaters or hot air guns - these may damage the coating.